



GVWR (lbs./kg) GROSS AXLE WEIGHT RATING (GAWR) (lbs./kg) ENGINE (Hino)

EXHAUST GAS AFTER-TREATMENT SYSTEM MAX. OUTPUT (HP) MAX. TORQUE (lb.-ft.) TRANSMISSION FUEL TANK (ltr./gal.) 25,500 / 11,570 Front 8,000 / 3,630 Rear 17,500 / 7,940 J08E-WU Diesel, 6-cylinder, turbo intercooled, 7.7L DEF-SCR Dosing system

230 @ 2,500 rpm 520 @ 1,500 rpm 6-speed Allison 2200 RDS 189 / 50, aluminum (standard) SERVICE BRAKES*
WHEELS
TIRE SIZE

Hydraulic disc front and rear 19.5 inch x 6.75 inch, 8 stud disc 245/70R19.5

WHEELBASE/CA**

WB 175.0 187.0 205.0 217.0 235.0 253.0 271.0 **CA** 107.6 119.6 137.6 149.6 167.6 185.6 203.6

WB: Distance between the centerline of the front and rear axles.

CA: Distance from the back of the cab to the centerline of the rear axle.

^{* 258}LP models are also available with air brakes. See dealer for details. ** See dealer for wheelbase availability



GVWR (lbs./kg) GROSS AXLE WEIGHT RATING (GAWR) (lbs./kg) ENGINE (Hino)

EXHAUST GAS AFTER-TREATMENT SYSTEM MAX. OUTPUT (HP) MAX. TORQUE (lb.-ft.) TRANSMISSION FUEL TANK (ltr./gal.) DUAL ALUMINUM TANK 25,950/11,771 Front 10,000 / 4,540 Rear 19,000 / 8,620 J08E-WU Diesel, 6-cylinder, turbo intercooled, 7.7L DEF-SCR Dosing system

230 @ 2,500 rpm 520 @ 1,500 rpm 6-speed Allison 2200 RDS 189 / 50, aluminum (standard) 189 / 50 (optional)

SERVICE BRAKES WHEELS TIRE SIZE Hydraulic disc front and rear 22.5 inch x 8.25 inch, 10 stud disc 11R22.5

WHEELBASE/CA*

WB 175.0 187.0 205.0 217.0 235.0 253.0 271.0 **CA** 107.6 119.6 137.6 149.6 167.6 185.6 203.6

*See dealer for wheelbase availability

WB: Distance between the centerline of the front and rear axles.

CA: Distance from the back of the cab to the centerline of the rear axle.



GVWR (lbs./kg) GROSS AXLE WEIGHT RATING (GAWR) (lbs./kg) ENGINE (Hino)

EXHAUST GAS AFTER-TREATMENT SYSTEM MAX. OUTPUT (HP) MAX. TORQUE (lb.-ft.) TRANSMISSION FUEL TANK (ltr./gal.) DUAL ALUMINUM TANK 33,000 / 14,950 Front 12,000 / 5,440 Rear 21,000 / 9,530 J08E-VB Diesel, 6-cylinder, turbo intercooled, 7.7L DEF-SCR Dosing system

260 @ 2,500 rpm 660 @ 1,500 rpm 6-speed Allison 2500 RDS 189 / 50, aluminum (standard) 189 / 50 (optional) SERVICE BRAKES* Hy WHEELS 22 TIRE SIZE 11

Hydraulic disc front and rear 22.5 inch x 8.25 inch, 10 stud disc 11R22.5

WHEELBASE/CA**

WB 187.0 205.0 217.0 235.0 253.0 271.0 280.0 **CA** 119.6 137.6 149.6 167.6 185.6 203.6 212.6

WB: Distance between the centerline of the front and rear axles.

CA: Distance from the back of the cab to the centerline of the rear axle.

^{* 338} models are also available with air brakes. See dealer for details.

** See dealer for wheelbase availability



GVWR (lbs./kg) **GROSS AXLE WEIGHT** RATING (GAWR) (lbs./kg) **ENGINE (Hino)**

EXHAUST GAS AFTER-TREATMENT SYSTEM MAX. OUTPUT (HP) MAX. TORQUE (lb.-ft.) **TRANSMISSION FUEL TANK (ltr./gal.)**

35,000 / 15,870 Front 13,200 / 5,990 Rear 23,000 / 10,430 J08E-VB Diesel, 6-cylinder, turbo intercooled, 7.7L **DEF-SCR** Dosing system

260 @ 2,500 rpm 660 @ 1,500 rpm 6-speed Allison 3000 RDS 189 / 50, aluminum, x 2 (standard) **SERVICE BRAKES** WHEELS TIRE SIZE

Full air 22.5 inch x 8.25 inch, 10 stud disc 11R22.5

WHEELBASE/CA*

WB 187.0 205.0 217.0 235.0 253.0 271.0 **CA** 119.6 137.6 149.6 167.6 185.6 203.6

HINO PREMIUM PROTECTION



HINO PREVENTIVE CARE



The Hino Preventive Care plan consists of the following items to protect your truck and enhance its longevity:

- 1 year scheduled maintenance, up to 50,000 kilometers
- Complimentary engine oil changes and chassis lubrication services for years 2 and 3, up to 150,000 kilometers: (Engine Oil, Transmission Fluid*, Differential Fluid and Chassis Lubrication)
- * Applies to cab-over engine models only



3 YEARS HINOWATCH ROADSIDE ASSISTANCE



HINOWATCH Roadside Assistance provides peace of mind driving since our customers know that assistance is only a toll-free phone call away. For the first 3 years of ownership, **HINOWATCH** protects your Hino truck with 24-hour roadside assistance at no extra charge. HINOWATCH covers the following: lockout service, out of fuel/DEF, battery jumpstart and towing on warrantable repairs (up to a maximum of \$1,000 per tow).

5 YEAR WARRANTY



Protecting your investment, Hino provides quality products backed by a comprehensive warranty!

Hino's legendary 7.7 litre J08E engine is covered by a 5-year / 400,000 km warranty.

Any remaining balance of Hino's warranty is fully transferable to the new owner if you sell your vehicle, adding to its resale value.



HINO GENUINE PARTS

Hino Genuine Parts have been designed and tested to meet stringent quality control standards to ensure they provide the best value and performance for your Hino truck.



HINO 3 YEAR PARTS WARRANTY

Introducing Hino's new 3 year, unlimited mileage warranty on all Hino parts, installed at any Hino dealership across Canada. This new industry-leading warranty is another example of how we are dedicated to providing Hino Genuine Parts and committed to protecting your investment. A 1 year, unlimited mileage warranty applies for Hino parts sold over the counter.

Please contact your closest Hino dealership for further details.

^{*} See dealer for wheelbase availability **WB**: Distance between the centerline of the front and rear axles. **CA**: Distance from the back of the cab to the centerline of the rear axle.

WARRANTY COVERAGE



Conventional Model Trucks

Description	Months/ Mileage (km)	Description	Months/ Mileage (km
BASIC TRUCK COMPONENTS		CAB	
Provides warranty protection against defects in material and workmanship for 24 months/ unlimited mileage. Includes towing* to nearest Hino Dealer for warrantable failures. (Adjustments and expendables such as bulbs and fuses are covered for 90 days/ 5,000 km.	24 months/ Unlimited	Provides warranty protection against corrosion perforation of the cab structure for 60 months/ unlimited mileage.	60 months/ Unlimite
		AUTOMATIC TRANSMISSION: ALLISON 2000/3000 SERIES	
Batteries and radio are covered for 12 months).		Warranty covers repairs or replacement, at Allison	
* To a maximum of \$1000 per tow		Transmission's option, to correct any transmission malfunction resulting from defects in materials or	36 months/ Unlimite
ENGINE		workmanship for 36 months/ unlimited mileage. Allison Transmissions are warranted by Allison for the time and	30 mondis, ominic
Provides warranty protection against defects in material		mileage specified.	
and workmanship for 60 months/ 400,000 km for all of the internal engine components plus the following: cylinder	60 months/ 400,000 km	Transmission Options available for:	
olock, cylinder head, fuel supply pump, unit injectors, turbocharger and flywheel housing.		Hino Models 268 (with 253" and 271" wheelbase): Allison 2200HS Highway Series Hino Models 338 (with 253", 271" & 280" wheelbase): Allison 2500HS Highway Series	
turbocharger and hywneer housing.		Warranty covers repairs or replacement for an additional	48 months/ Unlimite
EMISSIONS WARRANTY		year, total 48 months/ unlimited mileage, to correct any transmission malfunction resulting from defects in materials	
Provides warranty protection against defects in material and workmanship for 60 months/ 160,000 km, whichever occurs first, for the emission control system.	60 months/ 160,000 km	or workmanship. Allison Transmissions are warranted by Allison for the time and mileage specified.	
		ANTI-LOCK BRAKING SYSTEM (ABS) AIR/HYDRAULIC	
FRAME RAILS AND CROSS MEMBERS		Provides warranty protection against defects in	36 th/ 400 000 l
Provides warranty protection against structural cracks in the frame and cross members caused by defects in material and workmanship for 60 months/ unlimited mileage.	60 months/ Unlimited	material and workmanship for 36 months/ 480,000 km, whichever occurs first, for the following components: wheel sensors, modulator valves and ECU.	36 months/ 480,000 l

